



SPLICING ACCESSORIES FOR THERMOPLASTIC WATERSTOPS



Vinylex Splicing Irons are specifically designed for welding thermoplastic waterstops and are constructed of the highest quality components for superior and long lasting performance.

- Peel and Stick Teflon Cover Provided
- 100% Factory Tested
- Heavy Duty Vinyl Grip
- Eight Foot Grounded Cord
- Standard 110/120vac 8 Amp
- Adjustable Temperature
- Individually Boxed

The temperature control is adjustable from 250°F to 500°F for various conditions and products. PVC waterstops require a temperature range between 350°F and 400°F. TPER Waterstops are welded at a temperature between 400°F and 410°F.

IRON SIZES AND REPLACEMENT COVERS AVAILABLE:

PRODUCT CODE	DESCRIPTION
213	4" X 14" LARGE IRON
237	Replacement Cover for 213
214	2" X 14" SMALL IRON
238	Replacement Cover for 214
215	9" X 9" SQUARE IRON
236	Replacement Cover for 215
216	6" X 14" X-LARGE IRON
239	Replacement Cover for 216



PVC WATERSTOP FABRICATIONS

Vinylex Waterstop & Accessories offers the most complete line of waterstop products available, including PVC, and TPER Waterstop Fabrications. Fabrications are strongly recommended and often specified to assure the integrity of transitions and intersections. Please contact us for more information.

Vinylex Waterstop & Accessories

3400 Tree Court Industrial Blvd. St. Louis, MO 63122

Phone (800) 325-3602

www.vinylexwaterstop.com

07/09