LT56 Laser Tool

3



Rugged Universal Laser Layout Tool






3

YEAR


WARRANTY


2-YEARS


Included Accessory























LT56 Package

LT56-2 Package with HR220 Receiver

Specifications		WARRANTY
Laser Power	Less than 1mw	2-YEARS NO COST
Class/Wavelength	Class 2 / 635nm	V
Batteries	Lithium-ion, 7200 mAh, 3.7 V	
Battery Life	1 beam - 45 hours 2 beam - 35 hours 3 beam - 25 hours	
Charge Time	12 hours (30 minute quick char will provide 2 hours operation w	
Battery Warranty	2 years	
Charger	Input: 100-240V AC 190 mA Output: 5V DC 800mA	
Out of Level Indication	Flashing beam - triple flash ever	ry 10 seconds
Self Leveling Range	$4^0\ \pm 1^0$ all direction	
Dust and Water Resistance	IP54	
Operating Temperature	-10° to 45° (14 °F to 113 °F)	
Storage Temaperature	-20° to 60° (-4 °F to $~140$ °F)	
Size (L x W x H)	152 x 116 x 84 mm (4.6 x 6.0	x 3.3 in)
Weight	0.67 kg (1.48 lb)	



Contact Information:

NORTH AMERICA Trimble Spectra Precision Division 5475 Kellenburger Road Dayton, Ohio 45424 U.S.A. Toll Free +1-888-272-2433 Fax +1-937-245-5489 www.spectralasers.com

EUROPE Trimble Kaiserslautern GmbH Am Sportplatz 5 67661 Kaiserslautern GERMANY Phone +49-6301-711414 Fax +49-6301-32213

© 2013, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo and Spectra Precision are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark office and in other countries. All other trademarks are the property of their respective owners. PN 022507-354 (11/13)





LT56 Laser Tool

Rugged Universal Laser Layout Tool

The LT56 provides three 360 degree planes of laser light. A horizontal plane and 2 vertical planes 90 degrees apart provide all the reference required for interior layout.

- Bright crisp laser lines extends the working range and are easy to see
- Lithium-Ion batteries provide 25 hour operating time - huge savings on battery cost compared to alkaline models and are ecological friendly
- Rugged and durable 3 foot (1m) drop specification means the LT56 can keep working even after minor accidents
- Versatile mounting accessory includes ceiling track, magnetic and tripod mounts with rotation and fine vertical adjustment
- The HR220 Line Receiver can be added for short range exterior layout and elevation control



Applications

