

Construction / Industrial Tools & Supplie s

PROPANE

40,000 BTU/HR **Forced Air Propane Heater** #DXH40FA

DEWALT

- Rugged two-piece split barrel, designed to make cleaning and maintenance easier and safer
- Piezo ignition built into the thermo electric safety valve for easy ignition and operation

125,000BTU/HR **Forced Air Propane** Heater #DXH125FAV

DEWALT

- Patented Quiet Burner Technology reduces the combustion and operation noise by up to 50%
- Continuous electronic ignition; power: 110v
- Output: 350cгм; run-time: 8_{HR}
- · Hose length: 20'

170,000 BTU/HR **Forced Air Propane** Heater #DXH170FAVT

DEWALT

- Patented Quiet Burner Technology reduces the combustion and operation noise by up to 50%
- Equipped with a 25°F-95°F thermostat
- Continuous electronic ignition; power: 110v
- Output: 450cFM



- Continuous electronic ignition
- Output: 100cfм; run-time: 12нк
- Heating area: 800FT2; tank size: 20LBS
- LP consumption rate: 1.9LBS per hour
- Regulator settings: 10psi
- · Hose length: 15'

• Regulator settings: 20psi

size: 40LBS

6.9_{LBS} per hour

• Heating area: 3,000_{FT}²; tank

• LP consumption rate: 4.6-

• Run-time: 17HR.; heating

• LP consumption rate: 5.8-

• Regulator settings: 20PSI

area: 3,500_{FT}²


• Tank size: 100LBS

8.1_{LBS} per hour

· Hose length: 20'



DEWALT \$28500



KEEP WARM THIS WINTER!

KEROSENE, PROPANE, AND ELECTRIC HEATERS

- maintenance free use • 1" diameter heavy duty tubular steel frame
- 20" x 5" quiet, steel mesh radiant burner
- Piezo ignition built into the thermoelectric safety valve for easy ignition and operation
- Output: 45,000 BTU/HR
- Run-time: 17HR; heating area: 3.500fT²
- Tank size: 20LBS
- LP consumption rate: 2.1LBS per hour
- Regulator settings: 28" WC PSI
- · Hose length: 20'

15,000 BTU/HR Single Tank Top Heater **#MH15T**

Mr. Heater

- For use with propane tanks
- · High, med, low regulator
- Match lit
- Outdoor use only

Double Tank

Top Heater



- Soft nose P.O.L.
- Tip over safety shut-off valve

35,000 BTU/HR **Portable Radiant Propane Heater** #HS35LP



- Tip over safety switch
- Thermoelectric safety valve
- Gas inlet pressure 27.5" WC PSI
- Requires a 20LBS propane tank
- Includes a 20' hose and regulator assembly





Mi? Heater 🛂

#MH30T

- For use with propane tanks
- · High, med, low regulator
- Match lit
- Outdoor use only
- Mounts a 20LB propane cylinder
- Soft nose P.O.L.
- · Operate one or two burners for multiple heat output combinations
- Tip over safety shutoff valve



- · Standing pilot for increased safety
- Comes with 12FT hose and regulator
- Piezo Ignition
- Heating area: 4,700_{FT}²
- Tank size: 100LBS
- Gas inlet pressure min: 15 psi

400,000 BTU/HR Forced Air **Propane Heater** #HS400FAVT



- Efficient and clean burning
- Heavy duty high output fan
- Automatic solid state ignition • Electrical input: 115v, 60Hz, 5.5A
- Output: 1,400cгм
- Heating area: 9,000FT2



- Tank size: 2* X 100LBS: *required
- LP consumption rate: 9.3-18.5LBS per hour
- Regulator settings: 20psi
- Hose length: 10'





- For use with propane tanks Soft nose P.O.L.
- · High, med, low regulator
- Match lit
- Outdoor use only
- 540° of heat: 360° burner head with 180° multidirectional bracket

45,000 BTU/HR Single Pivot Head Tank

- Tip over safety shut-off valve
- Direct connection to 20_{LB} propane cylinder



Prices and product availability are subject to change without notice. All specials and promotions limited to stock on hand. Call for current prices. McQuade & Bannigan Inc. is not responsible for typographical errors and we make every effort to ensure the accuracy of the information published in our catalogs, fliers, and website. The documents and graphics published may contain technical inaccuracies or typographical errors. McQuade & Bannigan Inc. reserves the right to revoke any stated offer and to correct any errors, inaccuracies or omissions 11.06.25


CORDLESS - PROPANE

6,000 / 12,000 BTU HR **Cordless Propane Radiant Heater** #DXH12B



DEWALT.

- Rugged handle with LED light bar
- · High speed fan
- Dual tank capacity for 7hr run-time Powered by the 20V MAX &
- 3 USB charging ports
- Tip-over safety switch



- CSA Certified Indoor Safe
- FLEXVOLT family of DEWALT







- DEWALT
- Quiet Burner Technology® 50% Quieter than a standard propane heater
- High temperature limit switch
- Heavy-duty handle
- Split barrel design for easy maintenance
- Hose & regulator included
- Works with all 20V Max® & FLEXVOLT® batteries
- Recessed controls
- Easy gas connection
- CSA certified

KEROSENE

75,000 BTU/HR Forced Air **Kerosene Heater** #DXH75KT





- Equipped with a 25°F-95°F
- thermostat · Continuous electronic ignition; power: 120v 60HZ
- Output: 240cгм



- Heating area: 1,750FT2
- Fuel consumption: .56GAL/HR; run time (full tank): 11HR
- Fuel tank: 6GAL

135,000 BTU/HR Forced Air Kerosene Heater #DXH135HD

DEWALT

- Equipped with a 25°F-95°F thermostat
- 10" flat free tires
- · Continuous electronic ignition; power: 120v 60нz

- Output: 300cfm Heating area: 3,375_{FT}²
- Fuel consumption: 1.0GAL/HR; run
- time (full tank): 14HR Fuel tank: 14GAL

190,000 BTU/HR Forced Air Kerosene Heater #DXH190HD

DEWALT



- Equipped with a 25°F-95°F thermostat
- 10" flat free tires
- Continuous electronic ignition; power: 120v 60Hz
- Fuel tank: 14GAL
 - Output: 450cгм; heating area: 4,700_{FT}²
 - Fuel consumption: 1.4GAL/HR; run time (full tank): 10нк

215,000 BTU/HR Forced Air Kerosene Heater #DXH215HD

DEWALT



• 10" flat free tires

thermostat

INDIRECT

- Continuous electronic ignition; power: 120V 60нz
- Output: 450cгм; heating area: 6.500FT2
- Fuel consumption: 1.6GAL/HR; run time (full tank): 8HR
- Fuel tank: 14GAL

ELECTRIC

5,100 BTU/HR 120v, 1.5kw Electric Heater #VOLT1.5



- For heating, drying, and ventilating
- Fast, high temperature rise
- 10' power cord
- NEMA 5-15P plug

- Integrated ambient
- Air flow 116cFM

Overheat protection at 104°F

- thermostat from 32°F-100°F



• 17 gal tank capacity

• Air flow 1060FM



Accessories

12" Single Duct Adapter #F105104

12" x 25' Flexible Heat Duct #F150040

HSP Pro-Series: Remote Analog Thermostat #F105108

30,700 BTU/HR 240v, 9kw Electric Heater #VOLT9





- For heating, drying, and ventilating
- Fast, high temperature rise
- 10' power cord
- Integrated ambient thermostat
- from 32°F-100°F
- Overheat protection at 104°F
- Air flow 350cfm • NEMA 14-50P plug

www.MQB.com SALES@ MQB.com

UTICA

1300 Stark St. • Utica, NY 13502 Ph: (315) 724-7119 • Fax: (315) 724-0171



WATERTOWN

22696 Murrock Circle • Watertown, NY 13601 Ph: (315) 788-2612 • Fax: (315) 785-0361

Signs.MQB.com Signs@ mqb.com

SYRACUSE

6300 E. Molloy Rd. • E. Syracuse, NY 13057 Ph: (315) 671-4400 • Fax: (315) 671-4404